

Philips  
Scart cable

5 m

Composite A/V + S-Video

SWV6335



## Enjoy the ultimate viewing experience

with this premium A/V cable

Take your components to optimum performance. This top-of-the-range cable offers the best connection for transferring audio/video signals between components.

### Enjoy better picture quality

- 24 carat gold-plated connectors optimise signal
- 4-Cut connectors for secure connections
- Split centre pin for better signal transfer
- 99.97% Oxygen-Free Copper (OFC)

### Protects against signal loss

- 100% aluminium shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper-braided shielding
- Foam Polyethylene (FPE) Dielectric

### Easy installation

- Colour-coded connectors for instant recognition
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

**PHILIPS**  
sense and simplicity

Scart cable  
5 m Composite A/V + S-Video

## Specifications

### Packaging Data

- Quantity: 1
- EAN/UPC/GTIN: 87 10895 93475 6
- Gross weight: 1.18 kg
- Tare weight: 0.21 kg
- Net weight: 0.97 kg
- Length: 330 mm
- Width: 255 mm
- Height: 120 mm

### Inner Box

- EAN/UPC/GTIN: 87 10895 97046 4
- Quantity: 2
- Gross weight: 3.16 kg
- Tare weight: 1.22 kg

- Net weight: 1.94 kg
- Length: 345 mm
- Width: 255 mm
- Height: 270 mm

### Outer Box

- EAN/UPC/GTIN: 87 10895 97047 1
- Quantity: 4
- Gross weight: 7.78 kg
- Tare weight: 3.9 kg
- Net weight: 3.88 kg
- Length: 530 mm
- Width: 365 mm
- Height: 290 mm

SWV6335/10

## Product highlights

### 24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

### 4-Cut connectors

4-Cut connectors ensure secure connections between your component and your cable.

### Split centre pin

The split centre pin allows for better signal transfer and an improved connection to the component inputs.

### 99.97% OFC solid conductor

99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

### 100% aluminium shielding

This protective layer of aluminium guards against electromagnetic interference for improved signal quality.

### Twisted high-purity OFC

This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

### Copper-braided shielding

This protective layer of copper blocks radio frequency interference for improved signal quality.

### FPE Dielectric

Foam Polyethylene (FPE) dielectric is a superior insulation material that protects against signal loss.

### Colour-coded connectors

Colour-coded connections make it easy to install your cable into the correct inputs and outputs

### Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

### Plug and play

Plug and play offers easy installation of components without time-consuming installations.



Issue date 2008-10-11

Version: 2.0.4

12 NC: 9082 100 06399  
EAN: 87 10895 93475 6

© 2008 Koninklijke Philips Electronics N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips  
Electronics N.V. or their respective owners.

[www.philips.com](http://www.philips.com)